



SIRAIR™
Engineered for Comfort

Airconditioners Midwall Split - Fixed Speed R410 Refrigerant



Mirror Panel

9000btu, 12000btu, 18000btu, 24000btu



Heating &
Cooling



Environmentally
Friendly

5 Year

Compressor Warranty*

*Terms and Conditions apply
Compressor brands may vary

Model		KFR-25GW/R410A	KFR-35GW/R410A	KFR-51GW/R410A	KFR-66GW/R410A	
Energy Efficiency Rating (EER)		AA	AA	AA	A	
Rated volt and frequency		Ph-V-Hz	220-240/50	220-240V/50Hz	220-240/50	
Cooling	Cooling capacity	W	2700	3590	5100	6100
	Cooling power input	W	840	1120	1740	2130
	Cooling current input	A	3.8	5.1	7.9	9.8
Heating	Heating capacity	W	2750	3790	5500	6600
	Heating power input	W	760	1050	1410	2250
	Heating current input	A	3.5	4.8	6.4	10.4
Max. input consumption		W	1150	1850	2400	2700
Max. current		A	5.8	9.9	12.5	15.2
Compressor	Model		ASM106V1VDZ	PA118M1C-4DZ2	PA200X2CS-4KU1	PH370G2CS-4MU1
	Type (Rotary, Piston, scroll)		Rotary	Rotary	Rotary	Rotary
	Brand		GMCC	GMCC	GMCC	GMCC
Indoor	Indoor Air Circulation	m3/h	500	550	800	900
	Indoor Noise Level dB	dB(A)	30-39	29-39	37-44	42-46
	Dimension (L×W×H)	mm	745×250×195	745×250×195	900×292×215	900×292×215
	Packing (L×W×H)	mm	835×330×278	835×330×278	983×377×300	1105×377×300
	Net/Gross weight	Kg	9/11	9/11	13/15	14/17.5
Outdoor	Outdoor Noise Level dB	dB(A)	51	54	54	54
	Dimension (L×W×H)	mm	700×225×500	715×235×540	795×255×540	850×295×605
	Packing (L×W×H)	mm	825×320×550	851×345×600	920×335×595	995×415×690
	Net/Gross weight	Kg	25/29	28/33	38/42	45/51
	Refrigerant type/weight	g	R410A/600	R410A/970g	R410A/1500	R410A/1850
Refrigerant piping /Connection wiring	Liquid side/ Gas side/Length	mm				
	Max. refrigerant pipe length /Max. difference in level	m				